



HardCore™

DENSIFYING TREATMENT

A deep penetrating densifier that fills voids, adds structure, and reduces porosity of floors.



WHY HARDCORE:

REDUCES POROSITY TO HARDEN SURFACE AND INCREASE DURABILITY

Lithium silicate and potassium silicate blend

PROLONGS SHINE AND STAIN RESISTANCE

TECHNICAL DATA

Description	Densifying Treatment
Appearance	Clear, colorless
pH ASTM E70-07	11.5
Flash Point	>200°F / >93°C
Viscosity (Brookfield) @ 68°F (20°C)	<100 centipoise
VOC 40 CFR Part 59 Subpart D	<50 g/L
Fragrance	No added fragrance
Density ASTM D1475-13 (2008)	8.9 lb/gal @ 68°F 1.06 kg/L @ 20°C
Solubility	Miscible in water

DIRECTIONS

Apply with a pump-up sprayer. Spread with a brush or broom to ensure uniform coverage.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

SURFACES



Product Code	422FS	422GL3
Volume	2.50 US gallons	1 US gallon
Shipping Package	2 x 2.5 gallons	3 x 1 gallon
Pallet Quantity	48	60